S1 Class

Hatch Openings (L X B (m))

CH No.2 (FWD): 12.87 x 8.46

CH No.2 (AFT): 12.87 x 11.10

CH No 3 - 5: 25.74 x 11.10

CH No 1: 5.25 x 11.00

Type Multi-purpose, Triple decker, Container/Bulk carrier

Built 2012 Class ABS

Notation +A1, Bulk Carrier, BC-A, E, +AMS, +ACCU, SH, GRAB(20), SHCM, TCM, ESP,

CPS, CRC, CSC, RRDA

Port of Registry Singapore

Description

Single screw, self-sustaining, multi-purpose conbulk vessel, with double skin, box shaped cargo holds and a double tier of flush removable tween decks.

Principal particulars

 LOA/LBP
 180.06m/169.5m

 Beam/Depth Moulded
 27.20m/15.26m

 Summer Draft
 10.500m

 GRT/NRT
 21164/9979

 Deadweight
 27230

Crane 1 & 3:60mt SWL @ 27m, 40mt SWL @ 37m

4.788m

Crane 2A & 2B: 45mt SWL @ 22m, 37mt @ 28m and 30mt @ 31m

Cranes 2A & 2B (Twin mode): 90mt SWL @ 22m, 74mt @ 28m and 60mt @ 31m

Using a Team Beam, loads of up to 140 mt can be lifted using 3 cranes..

Cargo Holds

Freeboard

Cargo cranes

Grain Capacity 38585 cbm (excluding No 1 cargo hold)

Holds/Hatches 5 Holds / 9 Hatches
Ventilation Mechanical
Ventilation rate 15 air changes/hour

Features Certified for carriage of grain and bulk cargoes

The pontoons are stowed on deck and in No 1 cargo hold, converting CH 1 to 5 into single boxed shaped holds.

Certified for carriage of IMDG cargo.





