

## PAC LOMBOK

**Type** Steel General Cargo  
**Built** 2008  
**Class** GERMANISCHER LLOYD (GL)  
**Notation** (GL) +100 A5 E  
**Port of Registry** Singapore

### Description

Twin screw, multi-purpose vessel.  
 Designed and Constructed to carry containers, bulk cargo, grain in holds and containers on hatches and poop deck.

### Principal particulars

LOA/LBP 117m/110m  
 Beam/Depth Moulded 19.7m/8.50m  
 Summer Draft 6.45m  
 GRT/NRT 5316/2309  
 Deadweight 7600  
 Freeboard 2.072m

### Hatch Openings (L X B (m))

CH No 1: 19.5 x 15.0  
 CH No.2: 31.85 x 15.0  
 CH No.3: 25.35 x 15

### Cargo cranes

Crane 1 & 2 : 40mt SWL @ 2.5-28m on Portside deck.

### Cargo Holds

Container Capacity In Holds = 200 TEU Reefer Plug = 60  
 On Deck = 429 TEU  
 Holds/Hatches 3 Holds / 3 Hatches  
 Ventilation Motor  
 Ventilation Rate Capacity : 11000m3/h, Speed : 3500r/min, Power : 5,5 kW, Power source : 3φ, 440V, 60Hz  
 Features Certified for containers or carriage of grain and bulk cargoes  
 Hatch Cover Merk Mac Greggor Pontoon Type, non sequential opening possible

Admissible container stowage :	On Main Deck	On tank top	Tank top strength
			Bench on H3
20' Container	55 mtons per stack	60 mtons per stack	9.8 mt/m2
40' Container	70 mtons per stack	90 mtons per stack	5.4 mt/m2

